

SDS: A4248-E81US

Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

#### 1. Identification

Product name: ENEOS Gear Oil LSD 75W-90

Manufacturer/Supplier: ENEOS USA, Inc.

Address: 20 N. Martingale RD. Suite 325, Schaumburg, IL 60173

Charge section: Lubricants Sales Dept.

TEL (Information): +1-847-413-2188

Emergency Telephone 3E: 1-800-451-8346 Number (US and ID Number: 17406

Canada): Contact Available: 24/7/365

Recommended use and

restrictions on use: General industrial application

#### 2. Hazards identification

Classification of the chemical in accordance with OSHA Hazard Communication Standard (29 CFR § 1910.1200)

Hazard category Category

Flammable liquids No Classification

Skin sensitizer Category 1

Aspiration hazard No Classification

Label elements

Pictograms:



Signal word: Warning

Hazard statement: May cause allergic skin reaction

Precautionary statements:

Prevention Do not handle until all safety precautions have been read and

understood.

Wear protective gloves/protective clothing/eye protection/face

protection.

Do not allow the eyes to become exposed to the product. Do not

swallow the product.

Contaminated work clothing must not be allowed out of the

workplace.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Response If swallowed: Immediately call a poison center/doctor/...

If swallowed: Rinse mouth. Do NOT induce vomiting.



SDS: A4248-E81US Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

If the eyes are exposed to the product: Rinse the eyes with plenty

of running water and immediately contact a physician.

If on skin: Wash with plenty of water/...

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Storage The product must be stored in a cool, well-ventilated location

where it will not be exposed to direct sunlight.

Containers that have been opened must be tightly sealed.

Disposal Dispose of contents/container in accordance with

local/regional/national/international regulations.

If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with

usage.

Emergency overview: PBT or vPvB: Not applicable

# 3. Composition/information on ingredients

3.1. Substances Not Applicable

#### 3.2. Mixtures

Ingredients and Concentration

Chemical Name	Concentr ation wt.%	CAS#
Base 0il(s)	80-90	Trade Secret
Additives	<20	
Polysulfides, di-tert-Bu	2-4	Trade Secret
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	1-3	Trade Secret

## 4. First-aid measures

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for

breathing.

Cover the body with blankets to keep warm and quiet. If you feel

unwell, seek medical advice.

Skin contact: Immediately flush skin with large amounts of water.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.



SDS: A4248-E81US

Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

Eye contact: Rinse with clean water carefully for several minutes. Remove

contact lenses if present and if removal is easy, then continue rinsing. Rinse for 15 minutes at a minimum and seek medical

attention.

Ingestion: Do not induce vomiting. Drink [one glass] [two glasses] of water.

Call a physician [or poison control

center] immediately.

Most important symptoms/effects,

acute and delayed.

May cause allergic skin reaction. Dermatis. Rash.

Protection for first aid person: No information.

## 5. Fire-fighting measures

Suitable extinguishing media: Mist of loaded liquid, dry chemicals, carbon dioxide, fire foam,

and dry sand are effective.

Unsuitable extinguishing media: Use of straight stream of water can cause a risk of spreading

fire.

Specific hazards arising from the

chemical:

In some cases of fire, may release irritant gases.

When burnt, may generate carbon monoxide and other toxic gases.

Specific extinguishing methods: Spray water to the surrounding facilities for cooling.

Keep unauthorized persons off the site of occurrence of fire and

the surroundings.

Even after extinction, cool containers thoroughly with plenty of

water.

Special protective equipment and precautions for fire fighters:

Wear fire/flame resistant/retardant clothing.

Fight fire from windward direction while wearing protective equipment. If contact with skin is expected, wear impervious

protective equipment and gloves.

Use air-breathing apparatus and protective clothing whenever

necessary.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment when working.

Remove nearby potential ignition sources immediately.

When mist is generated, use respiratory equipment to prevent

inhalation of mist.

Do not touch or walk through spillage.

Pay attention to the site of spillage, which is slippery.



SDS: A4248-E81US Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

Environmental precautions: Prevent spreading of oil spill with earth and sand, sandbags, or

other proper materials and use care not to allow the oil spill to

flow to street drains, sewer systems, and rivers.

At sea, install oil spill containment booms to prevent spreading

of spills and absorb with absorption mat or other proper

materials.

Methods and materials for containment and cleaning up:

In case of spillage in small quantity, collect spillage by absorbing with earth, sand, sawdust, waste, or other proper

materials.

In case of spillage in large quantity, enclose with embankment to

prevent spreading of spillage and collect spillage in empty

containers to the extent possible.

Prevention of second accident: In case of spillage, immediately inform the organizations

concerned of the spillage to prevent possible accidents and

spreading of spillage.

Remove nearby potential ignition sources immediately and make fire-extinguishing agents available. Remove spillage completely,

and ventilate and clean the site and the surroundings.

### 7. Handling and storage

Handling

Technical measures: Contaminated work clothing must not be allowed out of the

workplace.

Keep away from any possible contact with sparks, open flames, and high-temperature materials, and do not allow release of vapor

without justification.

Use pumps or other proper equipment for taking out from containers. Do not siphon with your mouth using a tube. Do not

drink.

When mist is generated, use respiratory equipment to prevent

inhalation of mist.

In case of vapor/mist dispersion, install a closed system, local ventilation system, and/or other proper equipment for the sources

of vapor/mist generation.

Avoid rough handling of containers such as falling, dropping,

exposing to shock, and dragging.

Ventilation requirements:

Maintain adequate ventilation when handling indoors.

Precautions for safe handling:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Avoid falling, dropping, exposing to shock, or dragging of

containers.

Wash hands and face thoroughly after handling.

Be careful with fire.

Wear protective gloves when opening containers to eliminate a risk

of hand injury.



SDS: A4248-E81US

Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

Contact avoidance: Use care to keep away from any possible contact with halogens,

strong acids, alkalis, and acidifying substances.

Contact with and storage in the same location of halogens, strong

acids, alkali and oxidized substances must be avoided.

Hygiene measures: After handling Wash hands thoroughly.

Storage

Storage conditions: Store in a well-ventilated, cool, dry, dark place, protecting from

direct sunlight and keeping away from any potential ignition

sources and high-temperature materials.

Store tightly stopped after use to prevent possible contamination

with dust and moisture.

Preferably store locked up in a proper storage area.

Use spill-proof containers that are free of damage/corrosion.

Safety adequate container materials:

## 8. Exposure controls/personal protection

Appropriate engineering controls: In case of

In case of mist generation, enclose the source of mist generation,  $% \left( 1\right) =\left( 1\right) \left( 1\right)$ 

or install a ventilation system.

Install eye cleaning and body cleaning equipment near the handling

site.

Control parameters

Chemical Name		U.S OSHA			ACGIH	
		STEL	TWA	TLV-STEL	TLV-TWA	
Base 0il(s)	-ppm	-ppm	-ppm	-ppm	-ppm	
	-mg/m3	-mg/m3	-mg/m3	-mg/m3	-mg/m3	
Polysulfides, di-tert-Bu	-ppm	-ppm	-ppm	-ppm	-ppm	
	-mg/m3	-mg/m3	-mg/m3	-mg/m3	-mg/m3	
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	-ppm	-ppm	-ppm	-ppm	-ppm	
	-mg/m3	-mg/m3	-mg/m3	-mg/m3	-mg/m3	

Personal protective equipment

Respiratory Wear protective gloves/protective clothing/eye protection/face

protection: protection.

Not needed under normal conditions, but wear a gas mask (against

organic gases) whenever required.

Hand protection: Wear protective gloves/protective clothing/eye protection/face

protection.

In case of prolonged or repeated exposure, wear oil-resistant hand

protection.

Eye/face protection: Wear protective gloves/protective clothing/eye protection/face

protection.



SDS: A4248-E81US Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

In case of exposure to splashes, wear ordinary type goggles.

Skin protection: Wear protective gloves/protective clothing/eye protection/face

protection.

In case of handling over a prolonged period of time or in case of exposure to oil, wear oil-resistant, long-sleeved work clothing.

Hygiene measures: Take off contaminated clothing and wash thoroughly before reuse.

Wash hands thoroughly after handling.

### 9. Physical and chemical properties

Product

Appearance: Liquid Form: Liquid

Color: Light yellow Odor: Slight odor Melting point/freezing No data

point:

Initial boiling point No data

and boiling range:

Flammability (solid, No data

gas):

Upper/lower No data

flammability or
explosive limits:

Flash point: ≥180(°C)Cleveland Open Cup

Auto-ignition Estimate 200-410(°C)

temperature:

Decomposition No data.

temperature:

oH: No data

Kinematic viscosity: >20.5 (mm2/sec) (40°C) Solubility: water: Insoluble.

Partition coefficient: No data.

n-octanol/water:

Vapour pressure: No data

Density(g/cm3): 0.8696(15℃)

Vapour density: No data.

Particle No data

characteristics:

Relative density: No data.
Viscosity: No data.

## 10. Stability and reactivity



SDS: A4248-E81US

Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

Reactivity: Stable when stored or preserved in a dark place at room temperature. Chemical stability: Stable when stored or preserved in a dark place at room temperature.

Possibility of hazardous

Conditions to avoid:

reactions:

Contact with incompatible hazard substances

Prolonged heating, open flames, and ignition sources

Keep away from any possible contact with strong oxidizing agents.

Incompatible materials: Use care to keep away from any possible contact with halogens, strong acids,

alkalis, and acidifying substances.

Hazardous decomposition

products: When burnt, may release carbon monoxide and other gases.

### 11. Toxicological information

Symptoms related to the physical, chemical

and toxicological characteristics:

May cause allergic skin reaction. Dermatitis. Rash.

Delayed and immediate effects and also chronic effects from short- and long- term

exposure:

Short term exposure:

Potential immediate effects: No information Potential delayed effects: No information

Long term exposure:

Potential immediate effects : No information Potential delayed effects : No information

Product

Acute toxicity (oral): Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Acute toxicity (dermal): Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Acute toxicity (inhalation): Classification not possible (Gas)

Classification not possible (Vapour) Classification not possible (Dust/Mist)

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Skin corrosion/irritation: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Serious eye damage/irritation: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Respiratory sensitization: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Skin sensitization: Category 1

For mixtures, hazard category was identified based on the

classification criteria for mixtures.



SDS: A4248-E81US Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

Mutagenicity: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Carcinogenicity: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Reproductive toxicity: Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Target organ effect/Single

exposure:

Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Target organ effect/Multi

exposure:

Classification not possible

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Respiratory toxic: No Classification

For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Other information: No information for mixtures.

Ingredient
Base Oil(s)

Acute toxicity (oral): LD50:> 15000 mg/kg[rat]
Acute toxicity (dermal): LD50:> 5000 mg/kg[rabbit]

Polysulfides, di-tert-Bu

Acute toxicity (oral): LD50: 6500 mg/kg[rat]

### 12. Ecological information

Product

Ecotoxicity

Acute toxicity: Classification not possible

Fish acute toxicity: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Daphnia acute toxicity: No information.

Algae acute toxicity: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Chronic toxicity: Classification not possible

Fish chronic toxicity: For mixtures, hazard category was identified based on the

classification criteria for mixtures.

Daphnia chronic toxicity: No information.

Algae chronic toxicity: For mixtures, hazard category was identified based on the

classification criteria for mixtures.



SDS: A4248-E81US

Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

Persistence and degradability: No information available on mixtures

Bioaccumulative potential:

Mobility in soil:

Dangerous for the ozone layer:

Other impact:

No information for mixtures.

Classification not possible

No information for mixtures.

Ingredient

Polysulfides, di-tert-Bu

Ecotoxicity

Acute toxicity:

Fish acute toxicity: 96hLC50: 250~500 mg/L[Pimephales promelas], 96hLC50: >

1000 mg/L[Pimephales promelas]

Daphnia acute toxicity: 48hEC50:> 1000 mg/L[Daphnia magna]

Chronic toxicity: No Data

## 13. Disposal considerations

Disposal Dispose of contents/container in accordance with local/regional/national/international

methods: regulations

Every customer/user of the product should dispose of industrial waste on its own responsibility, otherwise it must rely on a company authorized by prefectural governor for treating industrial waste or a local public body involved in the disposal of industrial

waste for proper disposal.

Before disposal of used container, remove contents completely.

# 14. Transport information

IATA UN number: Not regulated

Proper Not regulated

shipping name:

Packing Not regulated

group:

IMDG UN number: Not regulated

Proper Not regulated

shipping name:

Packing Not regulated

group:

Domestic restriction: No information.

Specific security Transport containers without causing any significant friction or shaking.

precaution and condition

of transportation:



SDS: A4248-E81US

Date Prepared: 2021/01/01

Date Revised:

Product Name: ENEOS Gear Oil LSD 75W-90

## 15. Regulatory information

US California Proposition 65

None present or none present in regulated concentrations

Superfund Amendments and Reauthorization Act of 1986 (SARA TitleⅢ)

None present or none present in regulated concentrations.

Australia (AICS):

Canada (DSL):

All components are listed or exempted.

China (IECSC):

All components are listed or exempted.

EU (REACH): In the case where one or more components are not listed or, even if listed,

in the case of importing to the country or area concerned, an application or

notification is required.

Korea (KECL):

All components are listed or exempted.

New Zealand (NZIoC):

All components are listed or exempted.

Philippines (PICCS):

All components are listed or exempted.

Taiwan (TCSI):

All components are listed or exempted.

USA (TSCA):

All components are listed or exempted.

#### 16. Other information

NFPA Health hazard rating blue:1,Flammability hazard rating:1

HMIS Health Ratings:1, Flammability Ratings:1

Date Prepared: 2021/1/1

Reference No information.

Disclaimer: We at ENEOS Corporation have prepared the copyrighted Safety Data Sheet to

provide reference information on the hazardous chemical product of interest

for our customers/users to ensure secure and safe handling.

We would like every customer/user of the product to refer to the information and understand the necessity of taking appropriate measures for the actual handling conditions on their own responsibilities for optimum practical

application of the product of interest.

Consequently, the Safety Data Sheet is not intended to guarantee the safety

of the product referenced to herein.